

App. No. 10/031287  
Office Action Dated April 9, 2004  
Amd. Dated July 8, 2004

### **REMARKS**

Reconsideration is respectfully requested in view of the above amendments and following remarks. Claims 1 and 11 are hereby amended. No new matter has been added. Claims 1-17 are pending.

The application is objected to because of alterations which have not been initialed and/or dated as required by 37 C.F.R. 1.52(c). A copy of the specification as originally filed is enclosed. A properly executed oath or declaration which complies with 37 CFR 1.67(a) and identifies the application by the application number and filing date is required. Applicant is hereby submitting a properly executed Combined Declaration & Power of Attorney.

The arrangement of the specification is objected to because of the lack of headings. The specification has been amended to add headings where appropriate. A Marked-up copy and clean copy are enclosed. Removal of the objection is requested. No new matter has been added.

Applicant appreciates the Examiner's indication of allowable subject matter in claims 6-8 and 11.

### **Claim rejections - 35 U.S.C. § 112**

Claim 11 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite. Claim 11 has been amended to read "a side hinge means". Applicant does not concede the correctness of the rejection. Withdrawal of the rejection is respectfully requested.

App. No. 10/031287  
Office Action Dated April 9, 2004  
Amd. Dated July 8, 2004

**Claim rejections - 35 U.S.C. § 103**

Claims 1-5, 10, 12-15 and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Queveau (US 4,664,437). Claims 9 and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Queveau in view of Van Sandt (US 5,212,907). Applicant respectfully traverses the rejections, and respectfully requests reconsideration in view of the following. Claim 1 has been amended to recite " an openable screen element unit in a building structure for insertion in an opening of a wall in said building structure, said screen element unit". Queveau teaches a screen element as a hatchback door for an automobile. Amended claim 1 teaches that the screen element is for a building structure. Moreover, Queveau does not teach the specific geometry of the screen element. The geometry of the screen element in the present invention ensures a communicative effect without being a hindrance to the functionality of the rooms on either side of the screen element. Applicant does not concede the correctness of the rejection. Withdrawal of the rejection is respectfully requested.

For at least these reasons discussed above, the cited art fails to render the present invention obvious under 35 U.S.C. 103, as neither Queveau nor Van Sandt alone or in combination, disclose or render obvious the above features of claim 1. It is therefore applicant's belief that claim 1 is allowable over the cited art for at least the above-cited reasons. Insofar as claims 2-17 depend directly or indirectly from claim 1, it is

App. No. 10/031287  
Office Action Dated April 9, 2004  
Amd. Dated July 8, 2004

applicant's belief that those claims are also allowable. Applicant does not concede the correctness of the rejection. Withdrawal of the rejection is respectfully requested.

In view of the above, favorable reconsideration in the form of a notice of allowance is requested. If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicants' primary attorney-of record, John J. Gresens (Reg. No. 33,112), at (612) 371.5265.





Dated: July 8, 2004

JJG:mmm

Respectfully submitted,

MERCHANT & GOULD P.C.  
P.O. Box 2903  
Minneapolis, Minnesota 55402-0903  
(612) 332-5300

By   
John J. Gresens  
Reg. No. 33,112



MARKED-UP COPY OF SUBSTITUTE SPECIFICATION

TITLE OF THE INVENTION

OPENABLE SCREEN ELEMENT SUCH AS A DOOR

CROSS-REFERENCE TO RELATED APPLICATIONS

Not Applicable

5 STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC

10 Not Applicable

FIELD OF THE INVENTION

The present invention relates to a screen element such as an insert unit to be inserted into an opening of a wall, especially a door or a window, comprising at least one screen element side-hinged to a frame-structure, said screen element being pivotally mounted  
15 over a hinge axis in a frame structure for opening and closing in a direction away from the opening.

BACKGROUND OF THE INVENTION

Buildings and building interior in general feature a wide variety of doors and windows in order to separate two rooms in a building structure. These doors may be of different  
20 shapes depending on their function, and include e.g. a fire door, gates, or main entrances to wall fronts providing access to a building. For interior use, they are used as room separators or fire doors in long corridors or walking areas of e.g. office buildings.

Interior doors may come in many shapes and sizes. Common to these door types is the fact that they consist of an essentially plate-shaped screen element in a hard material,

RECEIVED  
JUL 15 2004  
GROUP 3600

typically wood, glass, steel or aluminium or combinations thereof. The door plate is hinged to a frame-structure in the shape of a door case and is provided with a handle for opening and closing of the door. By larger openings, such as corridors, where division is required due to fire protection, double doors may be used.

- 5 The doors may be provided with various ornaments on the surface but they all have in common that they show a plane screening of the door opening.

- Other types of doors include flexible doors, such as folding doors, that do not open away from the opening, where a screen element of this kind may be folded when the door is opened since the door opening is provided with guiding rails at the top and bottom. A
- 10 folding door requires quite a lot of space when it is opened and is thus only advantageous if the wall opening is relatively wide and when one or two side-hung doors are not practical.

- Often, it will be practical to provide the wall immediately next to the door with a sign or the like, possibly extending out into the room, so that by-passers may determine where
- 15 they are. Also, the doors may be provided with special colours by which communication with the persons in the room (s) behind the doors may be established.

However, by the present invention it is realized that by departing from the traditional design of doors, this communication effect may be integrated in the door.

## BRIEF SUMMARY OF THE INVENTION

Thus, the present invention relates to a screen element of the initially mentioned kind comprising two mutually angled, planar sectional elements preferably rectangular in shape with differing planes and an intersection line which is essentially parallel with the  
5 hinge axis.

The first planar sectional element is preferably significantly wider than the second planar sectional element.

Apart from acting as communication surfaces bearing information about the persons in the room with one or more doors according to the invention integrated the walls, the  
10 screen element, such as the door plate of a screen element according to the invention, may also act as a direction pointer or provide visual indication of the direction in which the screen element may be opened (the door or the window) due to its bent shape. The two plane surfaces, which are mutually angled, also provide a light/shadow effect that may break the visual experience of the wall portion wherein the screen element is  
15 integrated.

In another embodiment of the invention, an openable screen element as the one disclosed above has been provided with lighting means and optional sensor means for activating the lighting means in the screen element or/and the frame structure. In this manner, it will also be possible to obtain a communicative effect for indication of the opening  
20 direction of the door and/or stating to which activity or person the room behind the door relates or belongs. In addition, it is possible to establish integrated lighting in e.g. the

frame above the door which will automatically be activated when activity outside the door is registered.

In the preferred embodiment of a screen element according to the invention, the two planar sectional elements are positioned in two planes with a mutual angle of  $10^{\circ}$  to  $20^{\circ}$ ,  
5 preferably around  $15^{\circ}$ . In this manner, a geometry is created whereby the screen element extends sufficiently out from the wall portion to ensure the communicative effect without the screen appearing as a hindrance to the functionality of the room and the door geometry appearing as a hindrance to the opening of the door.

In a preferred embodiment of a screen element according to the invention, the screen  
10 element is provided with a rebate along at least the side and top ends, said rebate having a complimentary cross section shape in relation to the cross section of the frame structure. In this manner, the frame will be covered and removed from the visual impression of the side of the room in which the door is opened.

In a first embodiment, the two planar sectional elements have two planes that both differ  
15 from the plane of the wall opening. This provides the opportunity to use both elements as communication surfaces.

In a second embodiment, the first planar sectional element has a plane parallel or coincident with the wall plane and the second planar sectional element has a differing plane. In this manner, the angled planar sectional element and the part of the frame  
20 structure connected herewith may be provided with communicative signalling means.

In yet another embodiment of an element according to the invention, the element contains two screen elements which are side-hinged at each side of the frame structure. In this manner, a double screen element, especially a double door, is provided and features a visual opening indication.

- 5 In a first embodiment of a double element according to the invention, the two screen elements have the same opening direction whereby the double door is suited for screening wide wall openings.

- In a second embodiment, the two screen elements have opposite opening directions. In this manner, a double door according to the invention is obtained which is particularly  
10 suited for e.g. a swing door solution, e.g. at the end of a corridor or the like, where many persons pass back and forth. With a screen according to this embodiment of the invention, the visual opening indication will be able to create a separation of traffic through the door opening and thereby minimize the risk of personal damage to people being in proximity to the door and especially in the opening direction of that door. This  
15 is made possible by the visual opening indicator with which the bent screen elements have been provided.

In a preferred area of use of an element according to the invention, the screen is a fire door.

- In another aspect of the invention, the screen element of the door has at least one internal  
20 space between two outer surfaces wherein internal automatic door closing means connected with the side hinge means have been arranged. Hereby, it is possible to shield



not only the frame of a fire door but also the automatic door closing means so that it does not appear disruptive for the visual impression of the door.

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

In the following, the invention has been described in detail with reference to the drawings

5 in which

fig. 1 shows a door in a preferred embodiment of a screen element according to the invention,

figs. 2 & 3 show two alternative embodiments of the invention,

figs. 4 to 6 show three double embodiments of a screen element according to the invention, and  
10

fig. 7 shows a door according to another embodiment of the invention.

### DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows a screen element according to the invention in the shape of a door mounted in a wall opening 5. The door may either be an outer door or a door integrated  
15 in an interior wall construction. The special thing about this door is that it is designed with a "bend" since the main surface of the door has two planar sectional elements 1,2, mutually angled at an angle of 10° to 20°, and preferably 15°. The door surface is designed in a material that is bent or assembled in such a manner that the first planar sectional element 1 is wider than the second planar sectional element 2. By the first

planar sectional element 1, the door plate or the screen element is hinged at one side (see e.g. figs. 2 and 7) to a frame structure 3. At the opposite side, the plate is bent or in another way extended into the second planar sectional element 2, wherein a door handle 4 is mounted with locking means, such as a locking pawl. Corresponding locking means  
5 are mounted in the frame 3 for fixing and potentially locking the door in a closed position.

As shown in figs. 2 and 3, a screen element according to the invention may essentially be mounted in the wall opening 5 in two different ways. Fig. 2 shows a first possibility where the two surfaces 1,2 extend out into the room in which the door is opened. Thus,  
10 when in closed position, the two planar sectional elements are positioned in different planes from the wall plane of the opening 5. The other principal possibility of mounting a screen element according to the invention in a wall opening is to ensure that one of the planar sectional elements 1,2 is parallel with the wall plane. Thus, in fig. 3 the main plane, which is the first planar sectional element 1, is arranged parallelly with the wall  
15 plane.

As is apparent from figs. 2 and 3, the door may be provided with a rebate 10 whereby a tightening between the door 1,2 and the frame 3 may be established, just as the rebate 10 may be designed in such dimensions that the frame 3 may be entirely hidden behind the rebate 10.

20 Figures 4 to 6 show various embodiments of a double door by using a screen element according to the invention. The embodiment shown in fig. 4 is a double door element with two doors according to the invention opening in the same direction. The two doors

are laterally reversed in design so that the two "bent" sectional elements 2,2' angled in relation to the main planes the opening direction of the door element. The embodiment in fig. 5 shows a double door element with two doors according to the invention opening in opposite directions which has been created by making the doors similar in shape, the bend between the planar sectional elements 1,2, 1' and 2' respectively, and showing the opening direction of each of the doors constituting the double door. Figure 6 shows an embodiment where only one door is a screen element according to the invention. In this case, the other part 8 of the door may be blinded but may be opened if required, e.g. during transportation of particularly wide furniture, machines or the like through the door opening.

The doors illustrated in figs. 2 to 6 have all been provided with locking means and a door knob 4 at each side of the door. Naturally, by the invention, it is also realized that the doors may alternatively be provided with knobs on just one or none of the sides if required by the conditions.

Figure 7 shows various other aspects of the invention. In order to provide the door with a communicative effect, or improve this effect, the frame 3, the door planes 1,2 or the space immediately above the frame may be provided with lighting means 7 and optional sensor means for activating the lighting means 7 by e.g. activity outside the door. The lighting means may consist of light boxes 7, e.g. in the frame 3, or even directly in the wall opening. The light boxes 7 may be in the shape of signs, e.g. with a logo or bear information of the activity or person to which the room behind the door relates.

Alternatively or as a supplement, either one or both of the planar sectional elements 1,2 may be provided with signs in the shape of an inscription, logo or the like.

Figure 7 also illustrates the possibility of concealing automatic door closing means 9 in the door, just as it will be possible to use spring hinges 6. However, this presupposes that  
5 the door surface is of a certain robustness but will be particularly attractive in relation to a fire door, since the outer surfaces of a door according to the invention are designed in steel in the shape specified by this invention.

By the above-mentioned description of a screen element according to the invention, the invention relates to a door used either for interior room separation in buildings, internal  
10 or external fire doors, main doors and entrances etc. However, it is understood that the invention may also be used in relation to the design of windows in order to provide the corresponding built-in communicative effects described above in relation to a door.

## CLAIMS

1. An openable screen element such as an insert unit to be inserted into an opening of a wall, particularly a door or a window, comprising at least one screen element side-hinged to a frame structure, said screen element being pivotally mounted over a hinge axis in the  
5 frame structure for opening and closing in a direction away from the opening characterised by the screen element comprising two mutually angled, planar sectional elements preferably rectangular in shape, placed in different planes with an intersection line essentially parallel with the hinge axis.
2. A openable screen element according to claim 1, characterized by the two planar  
10 sectional elements being placed in two planes with a mutual angle of  $10^{\circ}$  to  $20^{\circ}$ , preferably around  $15^{\circ}$ .
3. An openable screen element according to claim 1 or 2, characterized by the screen element being provided with a rebate along at least the side and top ends, said rebate having a complimentary cross section shape in relation to the cross section of the frame  
15 structure.
4. An openable screen element according to claims 1 to 3, characterized by the two planar sectional elements having two planes that are both different from the plane of the wall opening.
5. An openable screen element according to claims 1 to 3 characterized by the first planar  
20 sectional element having a plane parallel or coincident with the wall plane and the second planar sectional element differing therefrom.
6. An openable screen element according to any of the preceding claims characterized by the element comprising two screen elements side-hinged at each side of the frame structure.

7. An openable screen element according to claim 6 characterized by the two screen elements having the same opening direction.

8. An openable screen element according to claim 6 characterized by the two screen elements having opposite opening directions.

5 9. An openable screen element such as an insert unit to be inserted into an opening of a wall, particularly a door or a window, comprising at least one screen element side-hinged to a frame structure, said screen element being pivotally mounted over a hinge axis in the frame structure for opening and closing in a direction away from the opening characterized by lighting means being arranged in connection with the screen element  
10 and/or the frame structure with optional sensor means for activating the lighting means.

10. A screen element according to any of the preceding claims characterized by the screen element being a fire door.

11. A screen element according to claim 10 characterized by the screen element of the door having a space between the two outer surfaces wherein automatic door closing  
15 means are arranged in connection with the side hinge means.

## ABSTRACT

The present invention relates to an openable screen element such as an insert unit to be inserted into an opening of a wall, particularly a door or a window, comprising at least one screen element side-hinged to the frame structure, said screen element being

5 pivotally mounted over a hinge axis in the frame structure for opening and closing in a direction away from the opening, where the screen element comprises two mutually angled planar sectional elements preferably rectangular in shape, positioned in different planes with an intersection line essentially parallel with the hinge axis. Apart from being communication surfaces containing information of the activities in a room with one or

10 more doors according to the invention mounted into the walls, the screen element, such as a door surface of a screen element according to the invention, will also be able to function as a direction pointer or provide visual indication of the direction for opening of the screen element (door or window) due to its bent shape. With the two planar sectional elements of the door being mutually angled, it is also possible to obtain a light/shadow

15 effect that will be able to break the visual experience of the wall portion wherein the screen element has been integrated.

## SEQUENCE LISTING

Not applicable